ENGLER VISCOMETER

Used to determine the specific viscosity of tars and their products. It includes a contact thermoregulator and stirring device. The thermometer is not included. See accessories.

- Power: 300 W
- Dimensions: 262x262x550 mm
- Weight approx.: 10 kg

ENGLER VISCOMETER

STANDARDS

- AASHTO T54
- ASTM D1665
- ASTM D490

ACCESSORIES

81-B0120/1

Testing flask 50 ml

81-B0120/2

Kohlraush calibration flask 200 ml

81-B0120/4

Strainer no. 50 ASTM

82-B0121/1MF

Engler viscosity thermometer ASTM 23C, range +18 to +28°C, mercury free with alternative liquid

82-B0121/2MF

Engler viscosity thermometer ASTM 24C, range +39 to +54°C, mercury free with alternative liquid

82-B0121/3MF

Engler viscosity thermometer ASTM 25C, range +95 to +105°C, mercury free with alternative liquid

82-B0121/4MF

Thermometer IP 76C range +10 to +55°C, mercury free with alternative liquid

ORDERING CODE

81-B0120/B

Digital Engler viscometer. 230V, 50-60Hz, 1ph.

81-B0120/BZ

Digital Engler viscometer. 110V, 60Hz, 1ph.