POKER VIBRATORS

Ideal for the internal compaction of concrete specimens both in laboratory and in site, and a good alternative to the traditional tamping bar especially when there are large number of specimen to be compacted.

Three versions available:

- mains operated
- petrol operated
- battery operated

SPECIFICATION

Models 55-	C0162/E C0162/EZ	C0163/C	C0162/BT
Tip dimension mm	Dia. 25x250	Dia. 25x250	Dia. 25x220
Flexible shaft length mm	2000	2000	-
Vibrations/min	12000	12000	13000
Power W	2300	1200	2 x 4.0 Ah Batteries
Weight approx. kg	8	12	3

STANDARDS

- EN 12390-2
- ASTM C31
- ASTM C192
- AASHTO T23
- AASHTO T126

FEATURES

- Wide range of solutions in terms of power supply: electrical, petrol or battery operated
- Lightweight instruments, easy to use and carry

ORDERING CODE

55-C0162/BT

Battery operated pocker vibrator, 13000 vibrations/min, 18 V, 2 x 4.0 Ah battery pack

55-C0162/E

Electric poker vibrator. 2000 W. 2000 mm flexible shaft. 220-240V/50-60Hz/1Ph

55-C0162/EZ

Electric poker vibrator. 2000 W. 2000 mm flexible shaft. 110V/60Hz/1Ph

55-C0163/C

Petrol operated poker vibrator. Flexible shaft 2 mlong, tip dia. 25 x 250 mm

POKER VIBRATORS