

SOIL EXTRUDER, HAND OPERATED

This hydraulic extruder can accommodate standard U4 tubes and a range of adaptors to extrude soil samples 35, 38, 101.6, 106 and 152.4mm dia. It can also be used to remove Marshall, Proctor and CBR specimens. Appropriate accessories and adaptors are available and have to be ordered separately. See accessories.



SOIL EXTRUDER, HAND OPERATED

SPECIFICATION

- Max load cap.: 60 kN (6000 kgf)
- Ram travel: 480 mm
- Dimensions: 1140x300x370 mm
- Weight approx. (without accessories): 50 kg

STANDARDS

- ASTM D1883
- ASTM D698
- BS 1377:4
- BS 1924:2
- BS 598:107

ACCESSORIES

16-T0082/A16

Extrusion extension for 450 mm long samples.

16-T0082/1

Adaptor for extruding soil samples 35, 38, 101.6, 106 and 152.4 mm dia. Total length 280 mm (approx)

16-T0082/3

Frame with adaptor for extruding one 38 mm dia specimen

16-T0082/4

Frame with adaptor for extruding three 38 mm dia tubes from U4 tube

16-T0082/5

Adaptor for extruding a soil sample from U4 tube

ORDERING CODE

16-T0082/A

Hand operated universal extruder

